



# 1D Wired Laser barcode scanner

## Features

- High resolution up to 4 mil.
- Multi - selection for different usage.
- Optional: auto-sensing and hands-free stand.
- Suitable for Supermarket, POS (Point-of-sales), inventory management or Document tracking.



## Scanners Specifications :

Model Name	<b>LS6300V / LS6320V</b>
Description	Cable / Auto-sensing

## Performance Characteristics

• Light Source	650 nm Laser Diode
• Depth of field ( There are +/- 1 cm tolerance )	20 - 430mm(0.33mm pcs0.9)
• Decode Rate	100 scans/sec
• Best Resolution	0.1 mm (4 mil)
• Print Contrast	30% or more
• Scan Angle	Roll: ±30° / Pitch: ±65° / Skew: ±55°
• Indicators	LED & beeper
• Interface	USB HID,USB Serial (by request)
• Auto-sensing (LS6320V)	Up to 150 mm
• Symbologies	EAN-13, EAN-8, UPC-A, UPC-E, Code 39, Code 11, ISSN, ISBN, Code 93, ITF-6, ITF-14, Codabar, Code 128, GS1 Databar, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, MSI

## Electrical Characteristics

• Input voltage	5 VDC ± 5%
• Current - operating	85mA max

## Physical Characteristics

• Dimension (L * W * H)	165 X 65 X 90 mm
• Weight	125 g +/- 5 g (No cable)

## User Environment

• Temperature-operation	0°C to 45°C
• Temperature-storage	-10°C to 60°C
• Humidity	5% to 85% relative humidity, non-condensing
• Ambient Light	Sun light up to 5000 Lux

*Product specification is subject to change without notice.*

**RIOTEC CO., LTD. 8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan**

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw