



Mobile barcode scanner for Android OTG devices

Features

- 1D Mini Mobile barcode scanners are designed for Android OTG devices especially.
- DC9253A: Plug & Play, No need extra driver
- Lightweight, ergonomically designed for easy operation
- With application, DC92xx series make Android OTG devices become data collector economically.



Specifications :

Model Name	DC9253A
Engine	Honeywell N4313

Performance Characteristics

• Light Source	650 nm Laser Diode
• Depth of Field	1D (40 mil Code 39): 734 mm
• Scan Speed	108±16 scans /sec
• Best Resolution	1D (4 mil) Code 39
• Scan Angle	Tilt : ±35° / Pitch : ±60° / Skew : ±65°
• Interface	Micro USB (USB_HID ,USB Serial <by request>)
• Print Contrast	≥ 20%
• Symbolologies	Codabar, Code11, Code128, Code32, Code39 ,Code93, EAN/JAN-13, EAN/JAN-8, GS1DataBar Expanded , GS1DataBar Limited , GS1DataBar Omnidirectional, GS1-128, interleaved 2 of 5, ISBT 128, Matix 2 of 5, MSI, NEC 2 of 5, Plessey Codes, Postal Codes, Straight 2 of 5 IATA, Straight 2 of 5 Industrial, Telepen, Tropic Code ,UPC-A, UPC-E0, China Post

Electrical Characteristics

• Input voltage	Smart Phone / Tablet Power
• Current - operating	< 200 mA

Physical Characteristics

• Dimension (L * W * H)	43 X 65 X 21 mm (without cable)
• Color of housing	Black
• Weight	20 g

Environment

• Temperature-operation	0°C to 50°C
• Temperature-storage	-10°C to 60°C
• Humidity-operation	5% to 95% relative humidity, non-condensing
• Ambient Light	100,000 lux (Direct Sunlight)

Decode Zone (DOF is measured at the office under 600 lux and by Standard barcode. There are +/- 10 mm Torrence. DOF may be also impacted by barcode quality and environmental conditions.)

• 4 mil Code 39	117 ~ 141 mm
• 5 mil Code 39	106 ~ 190 mm
• 7.5 mil Code 39	92 ~ 271 mm
• 10 mil Code 39	66 ~ 371 mm
• 15 mil Code 39	45 ~ 547 mm
• 40 mil Code 39	96 ~ 734 mm
• 13mil 100% UPC	52 ~ 457 mm

Product specification is subject to change without notice.

RIOTEC CO., LTD.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw