

Features

- The Smart Barcode Scanner is designed for Android/iOS phone use.
- Communication interface:
 BT communication: HID profile or SPP profile (for iOS/Android devices)
 Wired communication: USB OTG cable (for Android OTG devices)
- iLS6300FS with 1MB memory, supports data transmission & batch mode.
 1MB memory can save 65,000 EAN13 codes.
- Unique Scan Holder design makes smartphone & scanner combined easily & closely
- Cradle works as charging stand for both scanner & smartphone.



Scanners Specifications :

Model Name	iLS6300FS
Description	Bluetooth Laser Barcode Scanner
Engine	1D Laser Engine

Performance Characteristics

• Light Source	650 nm Laser Diode
• Depth of Field (13mil)	200 mm
• scan rate	60 scan /sec
• Best Resolution	0.1 mm (4 mil) - Code 39
• Print Contrast	40% or more
• Scan Angle	Yaw 65°, Rotation 30°, Pitch 55°
• Indicators	LED & beeper
• Auto-sensing	Up to 150 mm
• Interface	BT communication: HID profile or SPP profile (for iOS/Android devices) Wired communication: USB OTG cable (for Android OTG devices)
• Symbologies	Code39, Code39 Full ASCII ,Code32,UPC-A, UPC-E, EAN-13,EAN-8,Code93 , Code128,Codabar,Interleaved 2of 5, MSI,Code11 ,Matrix 2 of 5 ,ISBN, ISSN, ITF 14, ,GS1 Databar,GS1-128

Electrical Characteristics

• Input voltage	5 VDC ± 5%
• Current - operating	85mA max
• Radio Range (open area)	BT Class 1 (70~100m in open area, based on real operation environment)
• RF Frequency	2.4GHz
• Battery Type	AA NiMH rechargeable battery 1.2V x 2 (2.4V 2300mAH)
• Scans per charge	more than 25,000 scans when fully charged
• Charge Time	4 ~ 5 hours
• Memory capacity	1MB (can save 65,000 sets more EAN 13 barcode)

Physical Characteristics

• Dimension (L * W * H)	203 X 65 X 95 mm (for scanner)
• Weight	202 g +/- 5 g (for scanner), 225 g +/- 5 g (for cradle)

User Environment

• Temperature-operation	0°C to 50°C
• Temperature-storage	-10°C to 60°C
• Humidity-operation	5% to 95% relative humidity, non-condensing
• Humidity-storage	5% to 95% relative humidity, non-condensing
• Ambient Light	Fluorescent Light 300 lux to Sun Light 30000 lux

Depth of Field (DOF is measured at the office under 600 lux and by Standard barcode. There are +/- 10 mm Torrence. DOF may be also impacted by barcode quality and environmental conditions.)

• 4 mil Code39	30mm - 110 mm
• 5 mil Code39	30mm - 130 mm
• 13 mil EAN 13	30mm - 200 mm

Product specification is subject to change without notice.

RIOTEC CO., LTD. **8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan**

TEL : +886-2-8647-1828 FAX : +886-2-8647-1800
 E-mail : sales@riotec.com.tw Web : www.riotec.com.tw