

Features

- . Streamlined appearance, beautiful and small
- . Industrial-standard receipt/label printer
- . Shock-proof under 1.4M falling
- . Easy to load paper, Easy to operate
- . Use low power consumption machine core, longer printing time, better printing effect
- . Support printing while charging
- . USB+Bluetooth interface(standard configuration)
- . Support Bluetooth BT3.0 and BT4.0, Support Android and IOS interconnecting



Specifications

• Model Name	MP3000
• Interfaces	USB+ Bluetooth
• Print Command	ESC/JPL/TSPL/CPCL
• Print Method	Thermal Line Printing
• Print Speed	50-90 mm/sec
• Print density	576 dots/line
• Printing width	80mm
• Character Size	12*24 point
• Light status	Lack of paper, opening, power, failure, charging power, power shortage, normal, etc.
• Connecting Way	Android, IOS, PC/Windows
• Positioning ways	Reflective positioning
• Font library content	GBK/Unicode/UTF-8/Code page
• Bar-code Type	Supports all One dimensional codes / QR codes

Paper

• Paper Type	Thermal receipt/Label
• Paper width	79.5+/-0.5mm
• Roll Diameter	Max 50mm
• Paper Thickness	0.05-0.15mm

Electrical Characteristics

• Adapter power	Input AC110-240V; output DC9V/1A
• Battery Power	2200maH/7.4V; Lithium battery
• Full-power printing	150-180M
• Charging time	4 hours
• Input buffer	bytes 1.5K

Physical Characteristics

• Dimension (L *W *H)	130X120X60mm
• Unit Weight	436 g
• Mechanical properties	50KM
• Color	Black/Blue
• Bluetooth Effect Range	Around 6-9 meters(Depend)

Environment

• Temperature-operation	0°C to 45°C
• Temperature-storage	-20°C to 60°C
• Humidity	Working: 20%-85%; Storage: 5%-95%
• Warranty	12 months at least
• Certificates	Appearance patent /CCC/CE/FCC/ROHS
• Other Features	Paper detection, power detection, manual shut down

Packing List

• Thermal Printer	1 Piece
• Thermal Roll	W(80mm)*Dia(30mm)
• USB Cable	1*1.2M
• Adapter	1 Piece;
• Manual	1 Piece

Product specification is subject to change without notice.